

13 seats+ 2 (folding), 3 standing, 0 wheelchair places 13 seats + 0 (folding), 1 standing, 1 wheelchair place

Sustainable low entry bus for daily city routes



	BASE VEHIC	LE INFORMATION		
MERC	EDES-BENZ	Spi	Sprinter	
	Wheelbase, mm	4325		
DIMENTIONS,	Length, mm	7367		
WEIGHT	Width, mm	2020		
	Height, mm	2703		
	Weight, kg	5500		
	Electric engine	150 kW / 1250 Nm		
	Drivetrain	Direct shaft to rear axle		
	Battery pack	115 kWh (400V) scalable NMC battery		
	battery pack	technology		
	Charger power	19.8 kW charger	50 kW charger	
		AC (6 hours)	CCS (2.5 hours)	
POWERTRAIN				
	Safety	AVAS – pedestrian audible warning system		
	Service and	GSM service data transmitter (2-year		
	checks	subscription incl.)		
	Range	Up to 200 km (depends on weather conditions)		
	Top speed	70 km/h		

24 months or 150 000 km bus warranty 5 year or 150 000 km battery warranty

MAIN BASE VEHICLE				
ARTICLE	DESCRIPTION			
C6L	Multifunction steering wheel			
E1U	USB socket, 5 V			
F61	Rear mirror inside			
F68	Exterior mirror heated and electrically adjustable			
HH9	Air conditioner, semi-automatic controlled, TEMPMATIC HH2			
	Electrically powered auxiliary air heater			
RG3	Tyres 205/75 R16 C			
SB3	Suspension seat, comfort version, driver's seat F49			
	Windscreen, heated			
W61	Windows in tailgate / Rear doors			
H22	Back pane heatable H16			
	Heated seat for driver ERO			
	Basic fitting for radio XL4			
	5500 kg weight variant			

CONVERSION SPECIFICATION

Engineered and manufactured by

ALTAS AUTO

ARTICLE	DESCRIPTION	QUANTITY		
CONVERSION				
	Primary conversion CITYLINE.	1		
	- Electro installation, control unit with switches marked with corresponding			
	icons, power switch,			
	- General and night LED passenger compartment lighting mounted into profiles,			
1.05	- Thermal and sound insulation ,			
	- Passenger compartment walls and ceiling covered with upholstery or artificial			
	leather (fabric and colours are selected for particular passenger compartment			
	configuration)			
	- Floor covered with anti-slip PVC flooring- Hanging bars for standing passengers			
	SEATS			
	Intercity type seats Kiel Ligero seat			
2.01	upholstery with fabric standard leg	13		
2.01	and wall fixing 3 point safety belts			
	fixed backrest			
2.01 R	Flap seats Kiel Nemo	2		
	2 point safety belts	2		
	ENTRANCE & EMERGENCY EXITS			
3.13	Double electric door, 1200mm width, remotely operated	1		
3.07	Roof-hatch, 970x630 mm. Tempered glass	1		
3.16	Foldable ramp at the double door entrance	1		
	WINDOWS			
4.08	Panoramic double-glazed side windows	1		

	HEATING & VENTILATION	
5.04 R	Electric AC compressor 7 kW (400V)	1
5.05 R	Passengers compartment evaporator, cooling capacity 5 kW	1
5.09	Side ducts for conditioned air	1
5.10R	Interior electric liquid heater – 5 kW	2
5.14	Passenger compartment convecting heaters	3
5.18	Additional air ventilator in the saloon ceiling	1
	INTERIOR	
6.07	Windows partition finished in artificial leather	1
6.08	Rear doors finished in fabric trim	1
6.10	Glass separation wall behind the driver	1
6.26	Grab handle at the entrance	1
	ELECTRICS & LIGHTING	
7.08	Light intensity adjuster of the passenger cabin lighting, both day and night	1
	AUDIO & VIDEO	
8.17	CD player, Bluetooth, USB	1
8.07	Loudspeakers integrated into passenger compartment ceiling	6
	MISCELANIOUS OTHER EQUIPMENT	
9.09	Watch with STOP indication	1
9.11	STOP buttons in passenger compartment	7
9.21	USB socket in the passenger compartment	10
9.24	Interior mirror, spherical	1
9.30	Exterior plastic hood for LED destination sign, above windscreen	1
9.39	Glass-brake hammers, 2 pcs.	1
9.50	Box for additional equipment, front mounted, right side	1
	EXTERIOR	
10.05	Side body-skirts, body painted	1
10.03	Wheel covers	1
10.16	Decorative painting over the side windows and at the front part	1
	SPECIAL ADDITIONAL EQUIPMENT	
11.04	Q-straint 3 point fixation system	1
11.10	STOP buttons at each wheelchair place in passenger compartment	1
11.10	and at rear door outside	
11.13	Separation of the driver's workplace by a wall	1






OPTIONAL EQUIPMENT				
ARTICLE	DESCRIPTION	QUANTITY		
8.19	Flexible microphone for driver	1		
9.77	Emergency door opening indication	1		
9.47	Holder for 6kg fire extinguisher	1		
10.01	Body painted bumpers and plastic moldings	1		
10.08	Chrome front grill	1		
EV.01	Autonomous diesel heater Webasto 9 kW for driver and passenger compartment (together with present electric heater – 5 kW). Approved for HVO fuel.	1		
EV.02	Passengers compartment air conditioning, cooling capacity 11,5 kW, mounted with additional electric A/C compressor 5kW	1		

SCHEMES

SEATING SCHEME



Mobil: 070 7126088 Tel: 08 7451855 info@busscenter.se www.busscenter.se